

C4225 Log Data Report

Borehole Information:

Borehole:	C4225		Site:	216-U-12 Crib	
Coordinates (WA State Plane)	GWL (ft) ¹ :	Dry	GWL Date:	01/26/2004
North	East	Drill Date	TOC ² Elevation	Total Depth (ft)	Type
Not Available	Not Available	Jan. 2004	Not Available	50	Push Hole

Casing Information:

Casing Type	Stickup (ft)	Outer Diameter (in.)	Inside Diameter (in.)	Thickness (in.)	Top (ft)	Bottom (ft)
Ousing Type	Otickup (it)	(111.)	(111.)	(1111.)	(11)	(14)
Threaded steel	1 4	6 5/8	5 5/8	1/2	1 4	50

The logging engineer measured a sample of casing located in a lay-down area next to the borehole. Outside casing diameter was measured using a caliper. The measurements were rounded to the nearest 1/16 in.

Borehole Notes:

This push-hole is located at the 12 o'clock position about 19 ft north of the 216-U-12 Crib boundary. On the ground surface, there is a 0.5-ft-deep depression surrounding the borehole where the drill rig's mast stood. Zero reference is the ground surface.

Logging Equipment Information:

Logging System:	Gamma 1E		Type: SGLS (70%) 34TP40587A
Calibration Date:	01/2004	Calibration Reference:	GJO-2004-568-TAC
		Logging Procedure:	MAC-HGLP 1.6.5, Rev. 0

Spectral Gamma Logging System (SGLS) Log Run Information:

Log Run	1	2 / Repeat	3	
Date	01/26/03	01/27/03	01/27/03	
Logging Engineer	Spatz	Spatz	Spatz	
Start Depth (ft)	48.0	15.0	9.0	
Finish Depth (ft)	9.0	10.0	1.0	
Count Time (sec)	100	100	100	
Live/Real	R	R	R	
Shield (Y/N)	N	N	N	
MSA Interval (ft)	1.0	1.0	1.0	
ft/min	N/A ³	N/A	N/A	
Pre-Verification	AE068CAB	AE071CAB	AE071CAB	
Start File	AE070000	AE071000	AE071006	
Finish File	AE070039	AE071005	AE071014	

Log Run	1	2 / Repeat	3	
Post-Verification	AE070CAA	AE074CAA	AE074CAA	
Depth Return Error (in.)	0	N/A	0	
Comments	No fine-gain adjustment.	Repeat section	No fine-gain adjustment.	

Logging Operation Notes:

Zero reference was ground surface. Logging was performed with a centralizer installed on the sonde. Preand post-survey verification measurements for the SGLS employed the Amersham KUT (40 K, 238 U, and 232 Th) verifier with serial number 118. Logging started at the nearest 0.5-ft interval after reaching total depth. Maximum logging depth achieved was 48.0 ft.

Analysis Notes:

Analyst: Sobczyk Date: 1/28/04 Reference: GJO-HGLP 1
--

SGLS pre-run and post-run verification spectra were collected at the beginning and end of the day. All of the verification spectra were within the acceptance criteria. The peak counts per second (cps) at the 609-keV, 1461-keV, and 2615-keV photopeaks on the post-run verification spectra as compared to the pre-run verification spectra for each day were between 9.1 percent lower and 2.7 percent higher at the end of the day. Examinations of spectra indicate that the detector functioned normally during logging, and the spectra are accepted.

Log spectra were processed in batch mode using APTEC SUPERVISOR to identify individual energy peaks and determine count rates. Verification spectra were used to determine the energy and resolution calibration for processing the data using APTEC SUPERVISOR. Concentrations were calculated in EXCEL (source file: G1EJan04.xls). Zero reference was the ground surface. Based on the field measurements, the casing configuration was assumed as one string of 6-in. casing with a thickness of 1/2 in. to 48.0 ft (total logging depth). The dead time correction is applied when the dead time exceeds 10 percent. A water correction was not required.

Log Plot Notes:

Separate log plots are provided for gross gamma and dead time, naturally occurring radionuclides (⁴⁰K, ²³⁸U, and ²³²Th), and man-made radionuclides. Plots of the repeat logs versus the original logs are included. For each radionuclide, the energy value of the spectral peak used for quantification is indicated. Unless otherwise noted, all radionuclides are plotted in picocuries per gram (pCi/g). The open circles indicate the minimum detectable level (MDL) for each radionuclide. Error bars on each plot represent error associated with counting statistics only and do not include errors associated with the inverse efficiency function, dead time correction, or casing correction. These errors are discussed in the calibration report. A combination plot is also included to facilitate correlation. The ²¹⁴Bi peak at 1764 keV was used to determine the naturally occurring ²³⁸U concentrations on the combination plot rather than the ²¹⁴Bi peak at 609 keV because it exhibited slightly higher net counts per second.


Results and Interpretations:

¹³⁷Cs was the only man-made radionuclide detected in this borehole. ¹³⁷Cs was detected in the interval between 9 and 21 ft with concentrations ranging from 0.3 to 76 pCi/g. The maximum concentration was measured at 10 ft. ¹³⁷Cs was also detected at 29 and 41 ft at concentrations near the MDL (0.2 pCi/g). Examination of the gamma energy spectra indicates that the occurrence of ¹³⁷Cs at 29 ft is probably a statistical fluke, since a well-defined 662-keV photopeak is not evident. At 41 ft, a well-defined photopeak is evident at 662 keV, indicating that ¹³⁷Cs exists at that depth.


The plots of the repeat logs demonstrate reasonable repeatability of the SGLS data for the natural radionuclides at energy levels of 609, 1461, 1764, and 2614 keV and for 137 Cs at 662 keV.

¹ GWL – groundwater level ² TOC – top of casing ³ N/A – not applicable







C4225
Natural Gamma Logs




C4225 Combination Plot




C4225 Combination Plot



C4225
Total Gamma & Dead Time



C4225
Rerun of Natural Gamma Logs (15.0 to 10.0 ft)



C4225
Rerun of Man-Made Radionuclides

